



## GTS 300 HPE TOURING - TECHNICAL SPECIFICATIONS

<b>ENGINE</b>	4-valve 4-stroke single cylinder, electronic injection, catalysed hpe
<b>DISPLACEMENT</b>	278.3 cc
<b>BORE X STROKE</b>	75 mm x 63 mm
<b>MAX POWER AT THE CRANK SHAFT</b>	17.5 kW - 23.8 HP - at 8,250 rpm
<b>MAX TORQUE</b>	26 Nm at 5,250 rpm
<b>CONSUMPTION</b>	88mpg
<b>CO2 EMISSIONS COMPLIANCE</b>	74 g/km
<b>FUEL SYSTEM</b>	Electronic Injection
<b>COOLING</b>	Liquid
<b>STARTER</b>	Electric
<b>GEARBOX</b>	CVT automatic with torque server
<b>CLUTCH</b>	Automatic dry centrifugal with shock absorbers
<b>LOAD-BEARING STRUCTURE</b>	Sheet steel shell with welded structural reinforcements
<b>FRONT SUSPENSION</b>	Single arm with helical spring and hydraulic shock absorber
<b>REAR SUSPENSION</b>	Double hydraulic shock absorber with helical spring with preload adjustable in 4 positions
<b>FRONT BRAKE</b>	Stainless steel Ø 220 mm disc with hydraulic control
<b>REAR BRAKE</b>	Stainless steel Ø 220 mm disc with hydraulic control
<b>ABS/ASR SYSTEM</b>	ABS/ASR standard
<b>FRONT TYRE</b>	Tubeless 120/70 - 12"
<b>REAR TYRE</b>	Tubeless 130/70 - 12"
<b>LENGTH/WIDTH/WHEELBASE</b>	1,950 / 755 / 1,375 mm
<b>SEAT HEIGHT</b>	790 mm
<b>FUEL TANK CAPACITY</b>	8.5 litres
<b>EMISSIONS COMPLIANCE</b>	Euro 5