



GTS SUPERTECH 125 HPE - TECHNICAL SPECIFICATIONS

ENGINE	4-valve 4-stroke single cylinder, electronic injection, catalysed i-get
DISPLACEMENT	124.7 cc
BORE X STROKE	52 mm x 58,7 mm
MAX POWER AT THE CRANK SHAFT	10.3 kW – 13.81 HP - at 8,750 rpm
MAX TORQUE	11.1 Nm at 6,750 rpm
CONSUMPTION	117.5mpg
CO2 EMISSIONS COMPLIANCE	59g/km
FUEL SYSTEM	Electronic Injection
COOLING	Liquid
STARTER	Electric Start & Stop system
GEARBOX	CVT automatic with torque server
CLUTCH	Automatic dry centrifugal with shock absorbers
LOAD-BEARING STRUCTURE	Sheet steel shell with welded structural reinforcements
FRONT SUSPENSION	Single arm with helical spring and hydraulic shock absorber
REAR SUSPENSION	Double hydraulic shock absorber with helical spring with preload adjustable in 4 positions
FRONT BRAKE	Stainless steel Ø 220 mm disc with hydraulic control
REAR BRAKE	Stainless steel Ø 220 mm disc with hydraulic control
ABS/ASR SYSTEM	ABS standard
FRONT TYRE	Tubeless 120/70 - 12"
REAR TYRE	Tubeless 130/70 - 12"
LENGTH/WIDTH/WHEELBASE	1,950 / 755 / 1,380 mm
SEAT HEIGHT	790 mm
FUEL TANK CAPACITY	7 litres
EMISSIONS COMPLIANCE	Euro 5