



GTS SUPER RACING SIXTIES 300 HPE - TECHNICAL SPECIFICATIONS

ENGINE	4-valve 4-stroke single cylinder, electronic injection, catalysed hpe
DISPLACEMENT	278.3 cc
BORE X STROKE	75 mm x 63 mm
MAX POWER AT THE CRANK SHAFT	17.5 kW - 23.8 HP - at 8,250 rpm
MAX TORQUE	26 Nm at 5,250 rpm
CONSUMPTION	31.2 km/l
CO2 EMISSIONS COMPLIANCE	88mpg
FUEL SYSTEM	Electronic Injection
COOLING	Liquid
STARTER	Electric
GEARBOX	CVT automatic with torque server
CLUTCH	Automatic dry centrifugal with shock absorbers
LOAD-BEARING STRUCTURE	Sheet steel shell with welded structural reinforcements
FRONT SUSPENSION	Single arm with helical spring and hydraulic shock absorber
REAR SUSPENSION	Double hydraulic shock absorber with helical spring with preload adjustable in 4 positions
FRONT BRAKE	Stainless steel Ø 220 mm disc with hydraulic control
REAR BRAKE	Stainless steel Ø 220 mm disc with hydraulic control
ABS/ASR SYSTEM	ABS/ASR standard
FRONT TYRE	Tubeless 120/70 - 12"
REAR TYRE	Tubeless 130/70 - 12"
LENGTH/WIDTH/WHEELBASE	1,950 / 755 / 1,375 mm
SEAT HEIGHT	790 mm
FUEL TANK CAPACITY	8.5 litres
EMISSIONS COMPLIANCE	Euro 5