



V9 BOBBER - TECHNICAL SPECIFICATIONS

Engine	Transversal 90° V-twin, two valves per cylinder.
Cooling	air
Displacement	853 cc
Bore and stroke	84 x 77 mm
Maximum power	65 CV (47,8 kW) - 6.800 rpm (Also available at 35 kW, A2 driver license)
Maximum torque	73 Nm - 5.000 rpm
Compliance	Meets European Directive Euro 5
Emissions	119 g/km (CO2)
Consumption	4,9 l/100 km
Gearbox	6 speed
Fuel tank	15 l (4 reserve)
Seat height	785 mm
Dry weight	194 kg
Kerb weight	210 kg (According to guideline VO (EU) 168/2013 with all fluids, with standard equipment and fuelled with at least 90% of usable tank volume).
Front suspension	Hydraulic telescopic fork Ø 40 mm
Rear suspension	Swingarm Twin-sided with two spring preload adjustable shock absorbers
Front wheel	Lightweight alloy, 16" 130/90.
Rear wheel	Lightweight alloy, 16" 150/80.
Front brake	Stainless steel floating disk Ø 320 mm, Brembo caliper with 4 differentiated and opposed pistons.
Rear brake	Stainless steel disk Ø 260 mm, floating 2 pistons caliper.
Features	Full LED lights package with DRL, LCD dashboard, MGCT Moto Guzzi Controllo di Trazione, Standard double channel ABS.
Colour range	Nero Essenziale, Centenario.