



## TUAREG 660 - TECHNICAL SPECIFICATION

<b>Engine</b>	Parallel twin, 4 valves per cylinder, liquid-cooled with Ride-By-Wire
<b>Displacement</b>	659 cc
<b>Bore x stroke</b>	81 x 63.93 mm
<b>Max Power</b>	80 HP (59 kW) @ 9,250 rpm
<b>Max. Torque</b>	70 Nm @ 6,500 rpm
<b>Gearbox</b>	6 speed
<b>Clutch</b>	Multi plate wet clutch with slipper system
<b>Frame</b>	Trellis frame and aluminum plates
<b>Front suspension</b>	Kayaba Ø 43 mm USD fork, fully adjustable, 240 mm wheel travel
<b>Rear suspension</b>	Kayaba monoshock, fully adjustable, 240 mm wheel travel
<b>Front brake</b>	Double Ø 300 mm floating disc. Brembo calipers
<b>Rear brake</b>	Ø 260 mm disc. Brembo caliper
<b>Front wheel</b>	Spoked wheel with aluminum barrel 21" x 2.15"
<b>Rear wheel</b>	Spoked wheel with aluminum barrel 18" x 4.25"
<b>Seat height</b>	860 mm
<b>Fuel tank capacity</b>	18 litres
<b>Wet weight*</b>	204 Kg
<b>Standard Features</b>	Full LED headlights and indicators with light signature. Bonded 5" TFT dashboard. Engine Maps (AEM), Engine Brake (AEB), Dual-channel ABS (3 maps and Rear Wheel Lift-up Mitigation), Traction Control (ATC), 4 Riding Modes. Cruise Control (ACC). Metal Braided Brake Hoses

\*According to guideline VO (EU) 168/2013 with all fluids, with standard equipment and fuelled with at least 90% of usable tank volume